

TECHNICAL DATA

TAMPER

BT 60, BT 65



Maximum reliability and longevity
All around engine protection




More transparency
Hour meter RPM-meter with service indicator



Simple operation
Engine and fuel supply with combined switch

Shipping dimensions in cub.yd

BT 60 0.345
BT 65 0.345



Standard Equipment

- Engine Protection System
 - Protective engine covering
 - Two-stage double air filter system
 - Automatic oil level control
 - Dual fuel filter system
- Vibration insulated steering bow
- Self-cleaning air filter housing
- Protective covering
- Single point lifting device
- Recoil starter
- Plastic castor as loading aid
- Infinitely variable frequency
- Combination of engine stop/fuel switch
- h-/ rpm meter
- 3-2-1 Warranty

Optional Equipment

- Transport device with puncture proof wheels
- Tamper foot widths (6.3-13in)
- Tamper foot extensions
- Special painting
- Tool kit
- Service Kit
- Operator protection contact breaker switch
- TOUGH WARRANTY

Dimensions in in

	B	H	L	L1	W
BT 60	13.8	40.5	28.7	13.2	9.1
BT 65	13.8	40.5	28.7	13.2	11.0

Technical Data

		BOMAG BT 60	BOMAG BT 65
Weights			
Operating weight CECE	lb	128	150
Basic weight	lb	126	148
Dimensions			
Working width (tamper plate)	in	9.1	11.0
Driving Characteristics			
Working speed max.	ft/min	65.6	65.6
Area coverage max.	ft ² /h	2,970.9	3,616.8
Drive			
Engine manufacturer		Honda	Honda
Type		GXR 120	GXR 120
Emission stage		CARB Phase III	CARB Phase III
Cooling		air	air
Number of cylinders		1	1
Performance SAE J 1349	hp	3.8	3.8
Fuel		gasoline	gasoline
Drive system		mech.	mech.
Fuel comsump. aver. during operation	gal/h	0.2	0.2
Exciter system			
Frequency	vpm	600- 708	600- 708
Impact force	lb	3,372	3,822
Capacities			
Fuel	gal	0.8	0.8

Technical modifications reserved. Machines may be shown with options.



PRUS 541 13 010

190916 Sa

BOMAG Americas, Inc.
 125 Blue Granite Parkway
 Ridgeway, SC 29130
 USA
 Tel. +1 803 3370700
 Fax +1 803 3370800
 www.bomag.com/us

