

SPECIFICATIONS		BRUSHBULL™ SINGLE-SPINDLES			
MODEL	BB48.30	BB60.30	BB72.30	BB84.40	
Tractor PTO (hp)	15-50	25-50	30-75	35-90	
Hitch Category/Type	CAT 1 clevis			CAT 1 & 2 clevis	
Cutting Width (in)	48	60	72	84	
Total Weight with Chain Shield (lbs)	635	728	878	1,118	
Cutting Capacity Diameter (in)	2	2	2	2	
Cutting Height (in)	1 - 9			2 - 12	
Transport Width (in)	55	67.3	79.3	91.3	
Overall Length (in)	86	99	111	124	
Tractor PTO Speed (rpm)	540			540	
Quick-hitch Ready	Yes			Yes	
Rear Bumper	Z-channel			Z-channel	
Frame & Deck Support (in)	3 x 3 tube			3 x 3 tube	
Deck Construction	Smooth top, sloped			Smooth top, sloped	
Skid Shoes	Full-length, replaceable			Full-length, replaceable	
Deck Thickness (ga in)	12 .105		11 .120	11 .120	
Side Frame Thickness (ga in)	10 .135			10 .135	
Side Frame Depth (in)	10.5			11.6	
Gearbox Warranty	6-year limited			6-year limited	
Gearbox (hp)	65	65	75	90	
Output Shaft Diameter (in)	1.57			2	
Blade Tip Speed (fpm)	13,000	14,335	14,963	15,086	
Blade Dimensions (in)	.50 x 4			.50 x 4	
Blade Pin Diameter (in)	1.50			1.50	
Blade Carrier	Oval stump jumper			Oval stump jumper	
Driveline Protection	Slip-clutch			Slip-clutch	
Options	Check chain			Check chain, dual tailwheel	



SUPERIOR DESIGN

Customers like you told us what's important in a single-spindle cutter. Then, we redesigned our premium BrushBull cutter to meet – and exceed – your needs. An adjustable drive lift hanger and quick-hitch readiness make it easy to attach. A large access window on top of the deck and our exclusive, greasable Quick-change blade pins make blade changes easy, even in the field. But, you're not sacrificing performance for ease. A deep deck, large half-inch by four-inch blade and welded baffle work together, creating a strong suction that lifts, then evenly cuts and distributes large amounts of material.

SUPERIOR DURABILITY

Choose a BrushBull for the hours of testing in extreme conditions, and a Z-shaped, high-strength steel bumper that's twice as thick as competitive models, for added durability when backing over tough brush. Or, choose Woods for the advanced gearbox seal technology that's so good our 6-year limited warranty includes the seals. That's worry-free reliability.

SUPERIOR STYLE

Woods was the first to introduce a smooth, sloped deck that sheds debris. And, raising components off the deck makes clean-up easy. Front corners angle back to give operators more room between the tractor tire and cutter.

Adjustable driveline hanger makes it easier to attach, and is standard on all models.

Quick-hitch ready

Corners angle back to give operators more room between the tractor tire and cutter.

Full-length, bolt-on skid shoes protect the deck and are easy to change. Adjust the height on heavy-duty models.

Smooth, sloped deck sheds debris and is easy to clean.





New, advanced gearbox seal technology is designed for hard conditions, reduces leaks and downtime and is backed by our six-year gearbox warranty, which includes the seals.

Greasable Quick-change blade pins are easy to maintain and remove.



A large blade access window makes it easy to reach our exclusive Quick-change pins and quickly change the blade from the top of the deck.



BB60.30
Shown with optional chain shielding

High-strength steel bumper is 2-times thicker than competitive models, with a Z-channel frame for added durability when backing over tough brush.

SUPERIOR DESIGN, DURABILITY AND STYLE UNDER THE DECK, TOO!



- Rear baffle, standard on all models, concentrates the airflow and ensures cut material is distributed evenly.
- The large 1/2-inch by 4-inch blades and extra deep deck precisely cut large amounts of material.
- A beefier, heavy-duty crossbar and 1/4-inch steel stump jumper protect the undercarriage from extreme conditions.
- The frame is built with full-length 3-inch by 3-inch tubes and channels for extra durability.



WOODS BRUSH BULL