



SPECIFICATIONS PAGE

ADVANTAGE LOW PROFILE HD DUMP DUMP TRAILER



ADVANTAGE LOW PROFILE HD DUMP STANDARD FEATURES

Tubular Main Frame
102" Width
Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Zip Breakaway System
Breakaway Switch
Charge Wire with Circuit Breaker
7K Bolt-On Drop Leg Jack (12K on 146814LPHDT)
Slide-Out Ladder Ramps (6')
Triple-Acting Tailgate w/ Chains
Diamond Plate Fenders
EZ Lube Axles
Electric Brake Axles (2)
Nev-R-Adjust Brakes

Slipper Spring Suspension
Silver Wheels
Epoxy Primer
Polyurethane Paint Finish
Spare Tire Mount
D-Ring Tie-Downs - 1/2" (4)
Storage Tray
Sealed Wiring Harness
LED Lights – Rubber Mounted
Aluminum Lockable Pump Box
Remote Control with 20' Cord
12V Deep-Cycle Battery
HD Dual 3" Cylinders
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

ADVANTAGE LOW PROFILE HD DUMP DUMP TRAILER

	6'x12'	6'x14'
Model #	P126812LPHDT	P146814LPHDT
GVWR (lb.)	12000	14000
GAWR (lb. / Axle)	6000	7000
Curb Weight	3220	3560
Payload	8780	10440
Frame	6" x 2" x 3/16" Rec. Tube	
Crossmembers	3" Channel	
Tongue	5" Channel	
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring	
Jack	7K Bolt-On Drop Leg Jack	12K Bolt-On Drop Leg Jack
Fenders	Diamond Plate	
Axles	6,000 lb, Greased	7,000 lb, Greased
Suspension	Slipper Spring Suspension	
Tires	235/80R16 LRE	
Wheels	16"	
Volume Capacity	5.2 cu yd	6 cu yd
Lights	LED Lights - Rubber Mounted	
Electric Plug	7-Way SAE Plug	
Finish	PPG Industrial Polyurethane Paint	
Overall Length	198"	222"
Bed Width Inside	81.5"	
Bed Length Inside	144"	168"
Side Wall Height	20.5"	
Deck Height	28"	
Coupler Height	15" - 19"	
Gate	Triple-Acting Tailgate w/Chains	
Hydraulic Cylinder	Dual 3" x 36"	
Hydraulic Pump	12V Single Acting	
Battery	12V Deep-Cycle Battery	
Dump Angle	45°	43°

Specifications subject to change without notice.

