

ST TILT BED EQUIPMENT

		14K	16K
Model #	16'	ST8216TBE-B-140	ST8216TBE-B-160
	16' + 4'	ST82164TBE-B-140	ST82164TBE-B-160
	18'	ST8218TBE-B-140	ST8218TBE-B-160
	18' + 4'	ST82184TBE-B-140	ST82184TBE-B-160
GVWR (lb.)		14000	16000
GAWR (lb. / axle)		7000	8000
Curb Weight	16'	3120	3740
	16' + 4'	3520	4220
	18'	3320	4020
	18' + 4'	3730	4430
Payload	16'	10880	12260
	16' + 4'	10480	11780
	18'	10680	11980
	18' + 4'	10270	11570
Frame		6" C-Channel and Tube	8" C-Channel and Tube
Cross Members		3" C-Channel (16" On-Center)	
Tongue		6" C-Channel	8" C-Channel
Coupler		Adjustable 2-5/16" Coupler	Adjustable 4-Bolt Pintle Eye Coupler
Jack		Setback HD 12K Drop Leg Jack	
Fenders		HD Tread Plate	
Axles		Easy Lube Cambered Brake w/4" Drop	
Suspension		Slipper Spring	
Tires		235/80R16 LRE	215/75R17.5 LRH
Wheels		16", 8 on 6.5, Radial	17.5", 8 on 6.5, Radial
Decking		2 x 6 Treated Pine	
Lights		All LED Lights	
Electric Plug		7-Way RV-Style Molded Plug	
Finish		Powder Coated High Gloss Black	
Length (Overall/Tilting Deck)	16'	261" / 198"	
	16' + 4'	309" / 246"	
	18'	285" / 222"	
	18' + 4'	333" / 270"	
Between Fenders		82"	82"
Deck Height		20"	20"
Coupler Height		Adjustable 19"- 27"	
Tilt Angle		11.5 Degree Tilt Angle	

14K Models Include

Adjustable 2-5/16" Coupler and Setback HD 12K Drop Leg Jack

16K Models Include

Adjustable 4-Bolt Pintle Eye Coupler and Setback HD 12K Drop Leg Jack

TILT BED EQUIPMENT FEATURES

<ul style="list-style-type: none"> Tube Main Frame Nested Frame Tapered Entry for Full-Width Loading Full Wrapped C-Channel Tongue HD Tube Bulkhead Adjustable 2-5/16" Coupler (14K Models) Adjustable 4-Bolt Pintle Eye Coupler (16K Models) Safety Chains 	<ul style="list-style-type: none"> 7-Way RV-Style Molded Plug Breakaway Switch with Battery EverLink™ Wiring Harness Sealed Brake Connections Setback HD 12K Drop Leg Jack HD Reinforced Tread Plate Fenders HD Slipper Spring Axles 4" Drop Axles 	<ul style="list-style-type: none"> 8K Axle(s) with 3-3/8" Brake (16K Models) Easy Lube Hubs 16" Radial Tires (14K Models) 17.5" Radial Tires (16K Models) Silver Wheels Wheel Assembly, 235 80R16 LRE (14K Models) Wheel Assembly, 215 75R17.5 (16K Models) Powder Coat Finish 	<ul style="list-style-type: none"> Pressure Treated 2" x 6" Decking Rear Board Retainers HD Diamond Plate Knife Edge Tail (4) 1/2" D-rings (14K Models) (4) 5/8" D-rings (16K Models) Stake Pockets and Rub Rail Spare Tire Carrier All LED Lights Hydraulic Dampener
---	--	--	--

